RayGel Plus Joints

Easy Installation + Safe Operation = RayGel Plus





RavGel Plus Joints

RayGel Plus joints offer protection, insulation and high quality sealing for fast, easy and safe cable connections. The newly designed four types of joints offer a full range of branching capabilities from 2x1.5 to 5x16 mm² and are suitable for underground, direct buried and overhead applications.

Wide application area

- Street, garden and pool lighting
- Connection of outdoor equipment
- Cable trays and cable ducts
- For single-core cables from 10 - 50mm² and multi-core cables from 2 x 1.5 up to 5 x 16mm²
- With Raychem GelBox 25 joints up to 5 x 25mm² or 4 x 35mm²

7 E

Universal connector block

- Full range of branching capabilities without cutting of main cables
- Supplementary tool for insertion of sliding nuts
- Unique latchable connector block for even more effective and easy installation

Sophisticated enclosure design

- Optimized joint design with integrated strain relief and more space for the connection
- Flexible wave-like gel barriers (no tools required)
- Can be snap-closed by hand easily

- Covers and seals every connection quickly and easily, saving time and
 - Environment friendly 🔪

PowerGel sealant filled

- Rated to 90°C continuous
- ✓ IP68



APPLICATION Protection, isoland sealing, IP6 electrical conne up to 1kV.	ation • 1 Pow 58, • 1 univ ection and a • Tie w • Illustr	 KIT CONTENT 1 PowerGel sealant filled enclosure. 1 universal connector block including sliding nut insertion tool and allen key (for RayGel Plus joints 2 and 3). Tie wraps. Illustrated installation instructions. All joints are available in one piece packaging. 		Tyco Electronics Raychem GmbH Finsinger Feld 1 85521 Ottobrunn energy.te.com
	Article number	Connector	Application Range	
RayGel Plus O	CH6879-000	not included	Main-Cable: 2-3 x 1.5-2.5mm² (1 x 10-50) Branch-Cable: 2-3 x 1.5 mm² (1 x 10-16)	ENERGY
RayGel Plus 1	CH6880-000	not included	Main-Cable: 3-5 x 1.5-2.5 mm² (1 x 10-50) Branch-Cable: 3-5 x 1.5mm² (1 x 10-16)	
RayGel Plus 2	CH6881-000	included	Main-Cable: 3-5 x 1.5-6mm² Branch-Cable: 3-5 x 1.5-6mm²	
RayGel Plus 3	CH6882-000	included	Main-Cable: 3-5 x 6-16mm ² Branch-Cable: 3-5 x 6-16mm ²	